

# Fitting instructions: Solar Control Film

## Before you begin...

Please open your package and check your film carefully. If you find any creases, tears or other defects, please contact us immediately for advice. Do not remove the backing sheet or attempt to fit your film if you think it is faulty- we are unable to accept returns or provide refunds if installation has been attempted.

## You will need...







To complete your installation, you will need: a plant spray bottle and a small quantity of washing up liquid, sharp scissors, a sharp knife or blade, a tape measure and paper towels. You will also require the plastic squeegee which is supplied with your order.

## Prepare your window...

A clean window is vital to a successful installation. Take the time to clean your glass thoroughly before beginning the fitting process. Fill your spray bottle with water and add a few drops of washing up liquid.

## You are now ready to fit your film...

1. Measure your window and note down the measurement. Carefully unroll your film onto a clean, flat surface and using the sharp scissors, cut your film to a size slightly larger than your window.
2. Next, remove the backing sheet. Ensure you remove the sheet in a slow but steady fashion to avoid damaging the film.
3. Having removed the backing sheet, use your spray bottle to cover the entire surface of the film with soapy water solution. This helps to prevent the film becoming tangled and sticking to itself.
4. Cover the entire surface of your window with soapy water solution. The nature of the soapy water allows the film to be manoeuvred into place.
5. Pick up your film and apply it to your window. The soapy water solution on the film and the glass will allow you to slide it into the correct position.
6. Once in place, spray the entire surface with water. This will prevent friction between the squeegee and the film. Use your squeegee to push out any water or bubbles to the edge of the pane. Start at the top of the pane and work your way downwards.
7. Use your blade to carefully trim the excess film at the edges using the window frame as a guide. Your squeegee also provides a helpful edge to cut against.
8. Once the excess film has been removed, spray the film with the soapy water solution again. Use the squeegee to push any remaining moisture or bubbles to the edge of the window.
9. Use a paper towel to dry the window. Be careful not to lift the film at the edges or corners.



Visit our website  
for more!

Follow us on:

